

3M<sup>™</sup> DBI-SALA<sup>®</sup> Smart Lock Self-Retracting Lifelines

# Our smartest SRLs yet.

## 3M<sup>™</sup> DBI-SALA<sup>®</sup> **Smart Lock** Self-Retracting Lifelines

#### **Fewer unintentional lockups** -now that's smart.

Unlock your productivity. From reducing unintentional lockups,\* to simplifying inspections, every detail of the new 3M<sup>™</sup> DBI-SALA® Smart Lock Self-Retracting Lifelines is designed to help increase your productivity and convenience.

## **3M's Science of Safety** at work.



How did we create an SRL that reduces unintentional lockups? Using advanced motion capture technology, 3M studied the way users work, move and interact with SRLs on a typical job site. This data helped us engineer an arrest mechanism designed to better accommodate your natural work motions-resulting in fewer unintentional lockups.\*

		The state
re-packed	Feature-	
Swive		
Ergor Design overhe	Q	
Magn The life reduce (compa	U	
users to asset ir	E E E E E E E E E E E E E E E E E E E	
protect reduce	 ↓ ↓ 420 lb. (√)	/
⊼ົຸ— 1,350	420 lb.	/

#### SRLs for horizontal or vertical applications



nomic handle

ned for easy transport and support during ad installation.

#### netic retraction control

eline rewinds at an evenly controlled pace, helping e the possibility for harm to people or equipment ared to solutions with gear-based retraction).

#### nt pending dual label system ra label stored in the

er on the lifeline allows o easily access critical nformation and keeps it ted from damage to help e cost of ownership.



Ib. Maximum Arresting Force (MAF)

#### 420 lb. weight capacity\*

Highly-visible orange energy-absorber cover Identifies product as meeting Leading Edge standards and allows you to more easily confirm that workers are tied off (Horizontal models)

\* Requires 6 ft. of fall clearance for 311 lbs. - 420 lbs. users

### Horizontal

(Leading Edge)

 $\langle \bullet \rangle$ 



#### Fewer unintentional lock ups

Significant testing was completed to make this product work while reducing the unintentional lockups. Compared to our existing devices the new Smart Lock SRL locked up 29% less when tested against 422 work motion profiles.

Horizontal (Leading Edge)

ETT.









#### **Complies with OSHA** 1910.140 General Industry

Helps protect general industry workers up to 310 lbs. from falls when working with as little as 4 ft. of fall clearance.

## Unlock your productivity.

#### **Ordering Information**

3M <sup>™</sup> DBI-SALA <sup>®</sup> Smart Lock Self-Retracting Lifelines						
Application	Part #	Length	Lifeline Material			
Vertical (Overhead)	3503803	20 ft.	Galvanized Steel			
	3503804	20 ft.	Stainless Steel			
	3503800	30 ft.	Galvanized Steel			
	3503801	30 ft.	Stainless Steel			
	3503820	35 ft.	Rope			
	3503821	35 ft.	Stainless Steel			
	3503824	50 ft.	Galvanized Steel			
	3503823	50 ft.	Stainless Steel			
Horizontal	3503802	20 ft.	Galvanized Steel			
(Leading Edge)	3503822	30 ft.	Galvanized Steel			

**3M Fall Protection** 3833 SALA Way Red Wing, MN 55066 USA

3M

Distributed by Engineered Fall Protection Sales@EngineeredFallProtection.com www.EngineeredFallProtection.com Tel: (314) 492-4422

3M and DBI-SALA are trademarks of 3M Company and its affiliates. @ 3M 2018. All rights reserved.