

QUADRO

HORIZONTAL LIFELINE

TECHNICAL DATA SHEET



The Quadro is a temporary horizontal lifeline system designed to be used for restraint or fall arrest applications. Spanning up to 82ft / 25m the system can accommodate up to 4 users with a maximum user weight of 310lb / 141kg each.



Rope Vise Tensioner

The rope is tensioned by simply depressing and rotating the built-in handle. Tension can be safely removed by pulling the release arm.



Swivel Eye

Lightweight captive swivel eye prevents the rope from twisting during use.



Sewn Terminations

Stitched with contrasting thread for easy visual inspection.

NOTE: System length is measured between the bearing points of the anchor points, if using anchor straps ensure they do not extend the length of the system greater than 82ft / 25m.



Double Braid

5/8" / 16mm rope offers strength and durability by utilizing an outer sheath to protect the inner core.

QUADRO

HORIZONTAL LIFELINE

TECHNICAL DATA SHEET

SKU	Description	Span	Weight
30800	Quadro Horizontal Lifeline with Rope Vise Tensioner, Drawstring Rope Bag, 82ft Double Braided Rope, 4 x Aluminum O-rings, 2 x Steel Carabiners, 2 x Cross Arm Straps	82ft / 25m	18lb / 8.2kg



Features

- Inline swivel prevents rope from twisting
- Aluminum O-rings
- Steel carabiners
- Contrast color stitching for easy inspection
- Max Length
82ft / 25m
- Max Number of Users
4 in restraint or fall arrest with a maximum user weight of 310lb / 141kg each



Standards

- OSHA 1910
- OSHA 1926 Subpart M

