

Deluxe Tux Harness

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-2007, and ANSI A10.32-2012 regulations.

Custom configurations available. Not repairable.
Contact customer service for details.



Deluxe Tux Harnesses are suitable for the following applications:



Personal Fall Arrest: A Deluxe Tux Harness may be used in Personal Fall Arrest applications as a component of a Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', unless used in combination with equipment explicitly certified for extended free fall. Applicable D-ring: Dorsal.



Restraint: A Deluxe Tux Harness may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.



Work Positioning: A Deluxe Tux Harness, configured with side or shoulder D-rings, may be used in Work Positioning applications. Work Positioning systems allow a worker to be supported while in suspension and work freely with both hands. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. Maximum allowable free fall is 2'. Applicable D-rings: Side, Shoulder.



Rescue/Confined Space: A Deluxe Tux Harness may be used in Rescue/Confined Space applications. Rescue systems function to safely recover a worker from a confined location or after exposed to a fall. There are various configurations of Rescue systems depending on the type of rescue. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. No free fall is permitted. Applicable D-rings: Dorsal, chest, shoulder.

For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-420 lbs.

Materials: Nylon, Cotton Duck, polyester, and galvanized steel.

Always follow all manufacturer's instructions for proper adornment and use. Some steps of adorning a harness may require assistance from another person.

Upon completely adorning harness, Guardian Fall Protection recommends that another person, with knowledge of the safe and correct use of harness, inspect to ensure the harness is being worn correctly.

Features ANSI 107-2010 Class II compliant reflective webbing, and multiple equipment pockets for phones, tablets, radios, flashlights, and more.

Part #	Sizes	Description
02150, 02151, 02153, 02153, 02154	S, M, L, XL, 2XL	Deluxe Construction Tux™ w/PT Chest, TB Legs, & Side D-rings. Orange.
02155, 02156, 02157, 02158, 02159	S, M, L, XL, 2XL	Deluxe Construction Tux™ w/PT Chest, TB Legs, & Side D-rings. Black.
02160, 02161, 02162, 02163, 02164	S, M, L, XL, 2XL	Deluxe Construction Tux™ w/PT Chest, TB Legs, & Side D-rings. Green.