

## Guardrail Outrigger

**Part #: 15160**

Compliant with all OSHA 1910 and OSHA 1926 Subpart M regulations when used as component of compliant guardrail system.



Guardrail Outrigger is suitable for the following application:



**Fall Prevention:** Guardrail Outrigger is intended for use in combination with the Guardian Fall Protection G-rail (part #s 15181, 15182, 15183, and 15202) for use in Fall Prevention applications. Fall Prevention systems are used in place of, or in addition to, Fall Arrest or safety netting systems. Fall Prevention systems are placed around the leading edges of any and all fall hazards to which a worker may be exposed to prevent a worker from going over an edge, and are therefore considered to eliminate the hazard. G-rail systems **MUST ONLY** be used for Fall Prevention applications. Personal Fall Arrest, Restraint, Work Positioning, Climbing, and all other systems or applications must **NEVER** be connected to G-rail systems. Use of equipment in unintended applications may result in serious injury or death.

Materials: powder-coated steel.

ALWAYS use Guardrail Outriggers at BOTH ends of any interruption in continuous guardrail sections, and at BOTH ends of a continuous guardrail section. Guardrail Outriggers must be installed perpendicular to a continuous guardrail run. Outriggers function to provide stability at guardrail system endpoints.

For use as outrigger **ONLY**. Not a guardrail!

Compatible with Guardian Fall Protection baseplate part #s 15178 and 15180.



15178



15180

UPC-A Code: 672421151601

