

Rescue Winch

Part #: 15028

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.4-2013, and ANSI A10.32-2012 regulations.

Rescue Winch is suitable for the following applications:

Material Hoist: The Rescue Winch may be used to lift and lower materials and equipment. A Competent Person **MUST** determine the safe and proper methods for equipment handling.



Rescue/Confined Space: The Rescue Winch may be used as a personnel hoist in Rescue/Confined Space applications. Rescue systems function to safely recover a worker from a confined location or after exposed to a fall. There are various configurations of Rescue systems depending on the type of rescue. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 pounds. No free fall is permitted. Applicable D-rings: Dorsal, chest, shoulder.



For use in Rescue/Confined Space applications, the Rescue Winch **MUST be used in combination with a complete Personal Fall Arrest System (PFAS) deemed compatible by a Competent Person.**

MAXIMUM material/equipment capacity is 310 lbs.

Worker capacity range (including all clothing, tools, and equipment) is 130-310 lbs.



WARNING Use of equipment in unintended applications may result in serious injury or death. Maximum 1 attachment per connection point.

Materials: ABS housing and 3/16" galvanized steel cable.

Cable length: 65'.

Use in combination with the Guardian Arc-O-Pod (part # 15030) and Tripod Adapter Bracket (part # 15027), both sold separately.

MAXIMUM 1 user per Rescue Winch.

UPC-A Code: 672421150284



Arc-O-Pod



Tripod Adapter Bracket